

Output Torque Range
30Nm to 118Nm

Ratio
5:1 - 120:1



Gearboxes

HPCPF60

Worm / Wheel Reduction

Hollow Input

WEIGHT	5.1 Kg
BACKLASH	0° 30' approx
HOURS LIFE	12000 hr
MAX INPUT SPEED	3000 rpm
MATERIAL:	
CASE MAT'L	Aluminium HE30TF
WORM MAT'L	817M40(EN24)
WHEEL MAT'L	Alum. Bronze (AB2) with Steel Hub
GREASED FOR LIFE	Shell Gadus



N.m.	RPM Input	Reduction ratio					
		10:1	12:1	15:1	20:1	30:1	60:1
Output Torque	3000	30	31	33	35	38	44
	2000	33	36	39	41	44	50
	1000	45	47	50	54	58	64
	500	58	60	62	65	69	73
	200	77	78	80	84	88	94
	100	88	89	91	94	97	102
	50	100	102	104	105	107	110
10	113	114	115	116	116	118	

DISCOUNTS	
1 - 5	List Price
6 - 19	-5%
20 - 49	-10%
50 - 99	-15%
100 +	-20%

PART NUMBER	Ratio	Max Input Speed	Max Output Speed	% Effi. at 1000 Rpm	Backdrive	PRICE EACH 1-5
HPCPF60-10	10:1	3000	300	90	YES	£399.71
HPCPF60-12	12:1	3000	250	89	YES	£399.71
HPCPF60-15	15:1	3000	200	85	YES	£399.71
HPCPF60-20	20:1	3000	150	85	YES	£399.71
HPCPF60-30	30:1	3000	100	78	YES/NO	£399.71
HPCPF60-60	60:1	3000	50	68	NO	£399.71
HPCPF60-S	5:1-120:1		SPECIAL RATIO			£467.02
HPCPF60-A	SPECIAL MINIMUM BACKLASH 0° 8' OF ARC					£611.66

Output Shafts: HPCP60-X (Single), HPCP60-DX (Double): See page 1.23.

Testing in your application is necessary. You will need to assess duty, cycles and confirm gearbox suitability with your own calculations. Torque figures are to be used for guidance only

Unit 14, Foxwood Industrial Park, Foxwood Rd. Chesterfield, Derbyshire S41 9RN
Telephone +44(0)1246 268080 Fax +44(0)1246 260003



1.15

Gearboxes PRECISION WORM GEAR REDUCERS HPCPF60