

Inline Spur Gear Reducers

Output Torque
0.99 - 3.38Nm

Ratio
2:1 - 9:1

Double or Single Shafted

K64 / XK64


K64 / XK64



WEIGHT	2.6 Kg
BACKLASH	3°- 6° Depending on Ratio
HOURS LIFE	12000
MAX INPUT SPEED	4000 rpm
MATERIAL :	
CASE MAT'L	Aluminium Body & Caps
GEAR MAT'L	High Carbon Steel 817M40 (EN24)
GREASED FOR LIFE	Shell Alvania

INLINE SPUR GEAR REDUCERS

Gearboxes



N.m.	RPM Input	Reduction ratio							
		2:1	3:1	4:1	5:1	6:1	8:1	9:1	
Output Torque	4000	0.99	0.96	0.86	1.13	1.05	1.19	1.20	
	2000	1.26	1.22	1.08	1.32	1.22	1.35	1.38	
	1000	1.49	1.44	1.28	1.50	1.35	1.56	1.61	
	500	1.70	1.65	1.47	1.71	1.52	1.76	1.82	
	200	1.98	1.92	1.71	2.03	1.80	2.09	2.15	
	100	2.25	2.18	1.95	2.30	2.00	2.37	2.48	
	50	2.52	2.45	2.19	2.52	2.30	2.70	2.85	
	20	3.00	2.93	2.61	3.00	2.70	3.15	3.38	

specified when ordering.

*Plain bore, no keyslot

DISCOUNTS	
1 - 5	List Price
6 - 19	-5%
20 - 49	-10%
50 - 99	-15%
100 +	-20%

PART NUMBER	Ratio	Max O/P Speed rpm	N.M. Rating @ 1000 rpm	Mod.	Standard Direction	PRICE EACH 1-5
HPCK64-2 HPCXK64-2	2:1	2000	1.49	0.7	Same	£298.77
HPCK64-3 HPCXK64-3	3:1	1333	1.44	0.7	Same	£298.77
HPCK64-4 HPCXK64-4	4:1	1000	1.28	0.7	Same	£298.77
HPCK64-5 HPCXK64-5	5:1	800	1.50	0.7	Same	£298.77
HPCK64-6 HPCXK64-6	6:1	666	1.35	0.7	Same	£298.77
HPCK64-8 HPCXK64-8	8:1	500	1.56	0.7	Same	£298.77
HPCK64-9 HPCXK64-9	9:1	444	1.61	0.7	Same	£298.77
HPCK64-SP or HPCXK64-SP	Special Ratios: Replace SP with required ratio					£345.37

Other Info.

Testing in your application is necessary.

You will need to assess duty, cycles and confirm gearbox suitability with your own calculations.

Torque figures are to be used for guidance only.

Efficiency @ 1000 R.P.M.: 92%

1.66



Unit 14, Foxwood Industrial Park, Foxwood Rd. Chesterfield, Derbyshire S41 9RN

Telephone +44(0)1246 268080 Fax +44(0)1246 260003