

Mechanical

Rotary Dampers



Bi - Directional & Uni - Directional

HPCFRTK2

Body: Polycarbonate plastic



Gear: Polyacetal Plastic

Fluid: Silicone



Mechanical Rotary Dampers

Mechanical Rotary Dampers



Material: polycarbonate plastic
Temperature range: 0° C to 50° C

Weight max.: 0.116 kg

DISCOUNTS

Quantity	Discount
1 - 9	List Price
10 - 24	-10%
25 - 49	-15%
50 +	-30%

PART NUMBER			Damping Torque Ncm (Nom. 20 rpm, 23° C)	Price Each 1-9
Bi-directional damping	R-hand damping (clockwise)	L-hand damping (anti-clockwise)		
HPCFRTK2502			50 ± 10	£83.83
HPCFRTK2103			100 ± 20	£83.83
HPCFRTK2203			200 ± 40	£83.83
HPCFRTK2303			300 ± 80	£82.83
HPCFRTK2403			400 ± 100	£83.83
	HPCFRNK2R502	HPCFRNK2L502	50 ± 10	£92.28
	HPCFRNK2R103	HPCFRNK2L103	100 ± 20	£92.28
	HPCFRNK2R203	HPCFRNK2L203	200 ± 40	£92.28

6.46



Unit 14, Foxwood Industrial Park, Foxwood Rd. Chesterfield, Derbyshire S41 9RN

Telephone +44(0)1246 268080 Fax +44(0)1246 260003